Numerical analysis with the phase field equations for the Stefan problems

Jun-ichi Koga

Phase field equations describe the novel approach to the Stefan problems. We calculate these equations numerically performed in two-dimensions. We take full advantage of the phase field parameter φ to track the interface on which complicated movements or changes are needed. More precisely, we analyze the dissolution and/or precipitation without the unknown velocity functions like the Navier-Stokes equations numerically.

PACs numbers: v79B 68. 70. w+.

arXiv:1407.6464v3 [math.AP] 7 Feb 2016

I. INTRODUCTION

In these thirty years, it seems that phase field equations describe the novel approach to the Stefan problems. For example, it has been proved that the phase field equations converge to the equations of the Stefan problem as a singular limit. Caginalp and a co-researcher [1-4] have studied the reduction of these equations in the singular limit of Stefan problems and Hele-Shaw problem. The solution of the Stefan problem is obtained from the phase-field equations which consist the heat equation and the Ginzburg-Landau equation by Soner [10]. Hence, by the phase-field equations, we determine the sharp profile of the phase, the temperature distribution and the velocity of the moving interface between a solid and a liquid.
In this paper, using the Landau-Ginzburg theory of phase transition, physical properties show the phase field equations we consider, which is reduced to by the free energy

$$F(\varphi) = \int_\Omega dx \left[\frac{\epsilon^2}{2} |\nabla\varphi|^2 + W(\varphi) \right].$$

First we use the phase field equations of "Caginalp type" due to [2],

$$\begin{aligned} u_t + \frac{\ell}{2}\varphi_t &= \Delta u \\ \varphi_t &= \Delta\varphi + \frac{1}{2}\left(\varphi - \varphi^3\right) + 2u \end{aligned} \tag{1}$$

directly and numerically. Here $W(\varphi) =: \frac{1}{2}\left(\varphi - \varphi^3\right)$ is a derivative of a symmetric double-well potential with minima at ± 1, ℓ a latent heat and φ +1 liquid (e.g. water), −1 solid (e.g. ice). Second we investigate the following equations

$$\frac{\partial\varphi}{\partial t} = M_\varphi \left[\Delta\varphi + 4g(\varphi)\varphi\left(1-\varphi\right)\left(\varphi - 0.5 + \beta\right)\right] \tag{2}$$

in two space dimensions, where M_φ is a mobility of φ and these equations are called the modified Allen-Cahn equations. Third we consider the following equations due to [6],

$$\begin{aligned} \tau\frac{\partial\varphi}{\partial t} &= W^2\frac{\partial^2\varphi}{\partial x^2} + \left[\varphi - \lambda u\left(1-\varphi^2\right)\right]\left[1-\varphi^2\right], \\ \frac{\partial u}{\partial t} &= D\frac{\partial^2 u}{\partial x^2} + \frac{1}{2}\frac{\partial\varphi}{\partial t} \end{aligned} \tag{3}$$

Then applying the moving frame to these equations yields

$$\begin{aligned} \tau V\frac{\partial\varphi}{\partial x} + W^2\frac{\partial^2\varphi}{\partial x^2} + \left[\varphi - \lambda u\left(1-\varphi^2\right)\right]\left[1-\varphi^2\right] &= 0 \\ V\frac{\partial u}{\partial x} + D\frac{\partial^2 u}{\partial x^2} - \frac{V}{2}\frac{\partial\varphi}{\partial x} &= 0 \end{aligned} \tag{4}$$

Finally, we also use the following relations due to [8],

$$\begin{aligned} \frac{\partial\varphi}{\partial t} &= \frac{1}{Pe}\left[\nabla^2\varphi + \left(1-\varphi^2\right)(\varphi - \lambda c) - \kappa|\nabla\varphi|\right] \\ \frac{\partial c}{\partial t} &= \nabla^2 c + \alpha\frac{\partial\varphi}{\partial t} + \left(\nabla^2\varphi - \frac{\partial\varphi}{\partial t}\right)\frac{\alpha\cdot\dfrac{\partial\varphi}{\partial t}}{Da|\nabla\varphi|} \end{aligned} \tag{5}$$

to simulate the symmetric circular domain of solid. Here Pe is Péclet number, λ a positive parameter, κ a mean curvature, α also a positive parameter, Da a Damköhler number.
The so-called one phase Stefan problem has no discontinuous-gradient model for the temperature distribution. However, in the two phase Stefan problem, this phenomena occurs. Thus one can obtain the sharp-interface numerically by investigating what control it.
Our first purpose of this paper is to find out what determine the sharpness of the interface between two different phases (e.g. ice and water). The second is to investigate asymptotic behavior of the volume of the solidification and dissolution and/or precipitation.
We calculate these equations numerically performed in two-dimensions. We take full advantage of the phase field parameter φ to track the interface on which complicated movements or changes are needed. More precisely, we analyze the dissolution and/or precipitation without the unknown velocity functions like the Navier-Stokes equations numerically.

II. NUMERICAL METHOD

In our survey, we use the finite differential method for the time evolution equations numerically.
For Eqs. (1), we use the 5-point finite difference stencil

$$\Delta\varphi_{(i,j)} = \frac{\varphi_{(i+1,j)} + \varphi_{(i-1,j)} + \varphi_{(i,j+1)} + \varphi_{(i,j-1)} - 4\varphi_{(i,j)}}{(\Delta x)^2} \tag{6}$$

and we use the forward scheme in time

$$\frac{\partial\varphi}{\partial t} \cong \frac{\varphi^{(n+1)}_{(\ell,m)} - \varphi^{(n)}_{(\ell,m)}}{\Delta t}, \tag{7}$$

For Eq. (2), we use the forward scheme in time

$$\frac{\partial \varphi}{\partial t} \cong \frac{\varphi_{(\ell,m)}^{(n+1)} - \varphi_{(\ell,m)}^{(n)}}{\Delta t}, \tag{8}$$

on the other hand, the second order center-ward scheme in space

$$\begin{aligned} \frac{\partial^2 \varphi}{\partial x^2} &\cong \frac{\varphi_{(\ell-1,m)}^{(n)} - 2\varphi_{(\ell,m)}^{(n)} + \varphi_{(\ell+1,m)}^{(n)}}{(\Delta x)^2}, \\ \frac{\partial^2 \varphi}{\partial y^2} &\cong \frac{\varphi_{(\ell,m-1)}^{(n)} - 2\varphi_{(\ell,m)}^{(n)} + \varphi_{(\ell,m+1)}^{(n)}}{(\Delta y)^2} \end{aligned} \tag{9}$$

For Eqs. (3), the gradient of φ with respect to x, y, we use the central difference approximation

$$\begin{aligned} |\nabla \varphi|_{(i,j)} &= \frac{1}{\Delta x} \sqrt{\frac{\left(\varphi_{(i+1,j)} - \varphi_{(i-1,j)}\right)^2}{4} + \frac{\left(\varphi_{(i,j+1)} - \varphi_{(i,j-1)}\right)^2}{4}}, \\ |\nabla \varphi|_{(i,j)} &= \frac{1}{\Delta y} \sqrt{\frac{\left(\varphi_{(i+1,j)} - \varphi_{(i-1,j)}\right)^2}{4} + \frac{\left(\varphi_{(i,j+1)} - \varphi_{(i,j-1)}\right)^2}{4}}, \end{aligned} \tag{10}$$

respectively, and

$$\nabla^2 \varphi_{(i,j)} = \frac{\varphi_{(i+1,j)} + \varphi_{(i-1,j)} + \varphi_{(i,j+1)} + \varphi_{(i,j-1)} - 4\varphi_{(i,j)}}{(\Delta x)^2}. \tag{11}$$

If we do not have any confusion, we abbreviate the "(n)".

III. ASYMPTOTIC BEHAVIOR OF SOLUTIONS TO STEFAN PROBLEMS

This result is well-known. However we consider it to show an asymptotic behavior of the solutions for the Stefan problems.

In general, the parabolic partial differential equations often have initial-boundary value problems in a certain sense and the exact solutions are difficult to obtain by the direct calculations. Therefore the fact that we investigate the asymptotic behavior of solutions of general case plays an important rôle in this sense. Thus we get

$$s(t) \sim \beta t^{1/2} \tag{12}$$

where β corresponds to the integral formula "Gaussian distribution" (see Friedman, 1964, 2008).

IV. RESULTS AND DISCUSSIONS

TABLE I. Numerical volumes of the solidification and dissolution and/or precipitation for the time step. From the above, Eq. (1) v.s. Volume 1 and Eq. (2) v.s. Volume 2.

nstep	20	40	60	80	100	
Volume 1	4.8833	4.8848	4.8871	4.8899	4.8931	($\times 10^4$)
Volume 2	3.5925	4.0135	4.4569	4.9166	5.3904	($\times 10^4$)

We obtain the fact that the interface between two regions in the solidification and dissolution and/or precipitation are determined by the "coupling parameters" and coefficients, and sharp in our numerical simulation.

The volume controlled by the solidification and dissolution and/or precipitation is the dimensionless versions. we report that the volume of them is proportional to the time step (nstep in TABLE I).

FIG. 1: Profile of ϕ.

[1] Caginalp, G., Arch. Rational Mech. Anal., **92**, pp. 205-245 (1986)
[2] Caginalp, G., Phys. Rev. A., **39**, pp. 5887-5896 (1989)
[3] Caginalp, G., IMA J. Appl. Math., **44**, pp. 77-94 (1990)
[4] Caginalp, G., Chen X., Euro. J. Appl. Math., **9**, pp. 417-455 (1998)
[5] Carslaw, H., S., Jaeger, J., C., Conduction of heat in solids., Oxford : Clarendon Press. (1959)
[6] Karma, A., Rappel, W-J., Phys. Rev. E. **57** pp. 4323-4349 (1998)
[7] McFadden, G., B., Wheeler, A., A., Braun, R., J., Coriell, S., R., Sekerka, R., F., Phys. Rev. E., **48**, pp. 2016-2024. (1993)
[8] Friedman, A., Partial differential equations of parabolic type., Prentice-Hall, Englewood Cliffs, N. J., (1964) reprinted by Dover Publisher, New York (2008).
[9] Soner H., M., Arch. Rational Mech. Anal., **131**, pp.139-147 (1995)
[10] Xu, Z., Huang, H., Li, X., Meakin, P, **183**, Comput. Phys. Comm. pp.15-19. (2012)